

# CRD-1006

Cradle for OPH-1004  
and OPH-1005

USB

RS232



### + Product Specification

#### Communication

- **USB:** Version 2.0 Full speed, client, VCP, USB-A connector
- **RS232:** Baudrate 2400 bps - 115.2 kbps

#### Power

- **Voltage requirement:** 6V output for terminal charging, 4.2V output for battery charging
- **Battery Charging Time:** Maximum 2.5 hours

#### Durability

- **Temperature in Operation:** 14 to 113 °F (-10 to 45 °C)

#### Physical

- **Dimensions (WxHxD):** 2.68 x 2.76 x 3.78 in (68 x 70 x 96 mm)
- **Weight Body:** Ca. 3.9 oz (110 g)
- **Case:** ABS, Black

#### Regulatory and Safety

- **Product compliance:** CE, FCC, RoHS

#### Enclosed Items

- USB cable
- RS232 cable
- Power supply 100-240V/0.5A, 50/60 Hz, 6V/2A

Copyright 2015 Opticon. All rights reserved. This information is subject to change without notice. For availability, contact your local representative.

- **The Netherlands:** Hoofddorp  
- **France:** Issy Les Moulineaux  
- **Germany:** Dietzenbach  
- **Italy:** Castel Maggiore (BO)  
- **Sweden:** Järfälla  
- **United Kingdom:** Luton, Bedfordshire

- **U.S.A.:** Renton, WA  
- **Brazil:** São Paulo  
- **Japan:** Warabi City  
- **Taiwan:** Taipei  
- **P.R.China:** Shanghai

**Opticon, Inc.**  
2220 Lind Ave. SW, Suite 100  
Renton, WA 98057  
**Toll Free:** 800.636.0090  
**Local:** 425.651.2120  
**Fax:** 425.454.0865  
**Email:** Sales@OpticonUSA.com  
**Email:** Support@OpticonUSA.com

# OPTICON

WWW.OPTICONUSA.COM