

# CRD19E4

## Cradle for H19

### + Models

**CRD19** Single cradle, serial communication, charging

**CRD19E4** Multi-cradle, 4 slots, ethernet communication, charging

### + Specifications

#### Communication

- Ethernet: RJ45 Ethernet (LAN, UP-Link), 10/100 Base-T

#### Power

- Voltage requirement: 12V
- Battery charging time: Automatically determined

#### Durability

- Temperature in operation: 0 to 40 °C / 32 to 104 °F
- Temperature in storage: -20 to 60 °C / -4 to 140 °F

#### Physical

- Dimensions (w x h x d): 350 x 94 x 115 mm / 13.78 x 3.70 x 4.53 in
- Weight body: Ca. 670 g / 1 lb 7.6 oz
- Case: ABS, Black

#### Regulatory

- Product compliance: CE, RoHS

#### Enclosed items

- Power supply 100-240V/1.7A, 50/60 Hz, 12V/5A



Copyright Opticon. All rights reserved. This information is subject to change without prior notice. For availability, contact your local representative.

- **The Netherlands:** Hoofddorp  
- **France:** Issy Les Moulineaux  
- **Germany:** Dietzenbach  
- **Italy:** Castel Maggiore (BO)  
- **Spain:** Valencia  
- **Sweden:** Järfälla  
- **United Kingdom:** Luton, Bedfordshire  
- **U.S.A.:** Renton, WA  
- **Japan:** Warabi City

- **Taiwan:** Taipei  
- **P.R.China:** Shanghai  
- **Australia:** Kariong  
- **Brazil:** São Paulo

Opticon Sensors Europe B.V  
European headquarters  
Opaallaan 35  
2132 XV Hoofddorp  
The Netherlands  
phone: +31 (0)23-5692700  
fax: +31 (0)23-5638266  
email: sales@opticon.com  
internet: www.opticon.com