

IRU7000

Cradle for PHL7000 series

+ Specifications

Communication

- RS232: Baudrate 1200 bps - 115.2 kbps, D sub 9P M connector
- USB: Ver. 1.1, USB-A connector

Power

- Voltage requirement: 5V
- Battery charging time: Ca. 5 hours

Durability

- Temperature in operation: -10 to 50 °C / 14 to 122 °F
- Temperature in storage: -20 to 70 °C / -4 to 158 °F

Physical

- Dimensions (w x h x d):
73 x 134 x 143 mm / 2.87 x 5.28 x 5.63 in
- Weight body: 480 g / 1 lb 0.9 oz
- Case: ABS, Black

Regulatory & Safety

- Product compliance: CE, FCC, cUL

Enclosed items

- USB cable
- Power supply 100-240V/1.2A, 50/60 Hz, 5V/6.5A

Sold separately

- RS232 cable



Copyright Opticon. All rights reserved. This information is subject to change without prior notice. For availability, contact your local representative.

- **The Netherlands:** Hoofddorp
- **France:** Issy Les Moulineaux
- **Germany:** Dietzenbach
- **Italy:** Castel Maggiore (BO)
- **Spain:** Valencia
- **Sweden:** Järfälla
- **United Kingdom:** Luton, Bedfordshire
- **U.S.A.:** Renton, WA
- **Japan:** Warabi City

- **Taiwan:** Taipei
- **P.R.China:** Shanghai
- **Australia:** Kariong
- **Brazil:** São Paulo

Opticon Sensors Europe B.V
European headquarters
Opaallaan 35
2132 XV Hoofddorp
The Netherlands
phone: +31 (0)23-5692700
fax: +31 (0)23-5638266
email: sales@opticon.com
internet: www.opticon.com