

CRD-3301B

Cradle for OPI-3301i and OPC-3301i



Product Specifications

COMMUNICATION

RS232: 300 bps - 115.2 kbps

BLUETOOTH: Version 3.0 class 2, range up to 10m, 1 to 1 connection, slave mode, authentication and encryption

USB: Version 2.0, client, USB-VCP, USB-HID keyboard, USB-a connector

POWER

VOLTAGE REQUIREMENT: 6V \pm 5%

BATTERY CHARGING TIME: Maximum 5 hours with power supply, maximum 10 hours with USB bus power

DURABILITY

TEMPERATURE:

Operation: 32 to 104 °F (0 to 40 °C)

Storage: -4 to 140 °F (-20 to 60 °C)

HUMIDITY:

Operation: 25 - 85%

Storage: 20 - 90% (non-condensing)

PHYSICAL

DIMENSIONS (WXHxD): 3.94 x 3.07 x 7.28 in
(100 x 78 x 185 mm)

WEIGHT BODY: 8.5 oz (Ca. 240 g)

CASE: ABS, black or white

REGULATORY AND SAFETY

PRODUCT COMPLIANCE: CE, FCC, VCCI, RoHS, EN300 328, EN301 489

ENCLOSED ITEMS

POWER SUPPLY: 100-240V/0.5A, 50/60 Hz, 6V/2A

USB cable, RS232 cable