

CRD-27

Cradle for H-27

USB



+ Product Specification

Communication

- **USB:** Version 2.0, OTG, client and host, micro-USB connector

Power

- **Voltage Requirement:** 5V DC, 3A
- **Charging Method:** Battery in terminal or in spare slot

Durability

- **Temperature:**
Operation: 32 - 104 °F (0 - 40 °C)
Storage: -4 - 140 °F (-20 - 60 °C)

Physical

- **Dimensions (WxDxH):** 2.93 x 4.3 x 3.84 in (74.3 x 109.2 x 97.5 mm)
- **Weight Body:** 7.23 oz (205 g)
- **Case:** ABS/PC, black

Regulatory and Safety

- **Product Compliance:** CE, FCC, RoHS

Copyright 2015 Opticon. All rights reserved. This information is subject to change without notice. For availability, contact your local representative.

- **The Netherlands:** Hoofddorp
- **France:** Issy Les Moulineaux
- **Germany:** Dietzenbach
- **Italy:** Castel Maggiore (BO)
- **Sweden:** Järfälla
- **United Kingdom:** Luton, Bedfordshire

- **U.S.A.:** Renton, WA
- **Brazil:** São Paulo
- **Japan:** Warabi City
- **Taiwan:** Taipei
- **P.R.China:** Shanghai

Opticon, Inc.
2220 Lind Ave. SW, Suite 100
Renton, WA 98057
Toll Free: 800.636.0090
Local: 425.651.2120
Fax: 425.454.0865
Email: Sales@OpticonUSA.com
Email: Support@OpticonUSA.com

OPTICON

WWW.OPTICONUSA.COM