

CRD-32-E5

Cradle for H-32

Ethernet

+ Product Specifications

Communication

- Ethernet: RJ45 Ethernet (Ethernet LAN)

Power

- Voltage Requirement: 12V / 3.5A
- Charging Method: Battery in terminal

Durability

- Temperature:
Operation: -4 to 122 °F (-10 to 50 °C)
Storage: -4 to 140 °F (-20 to 60 °C)
- Humidity:
Operation: 20% to 85% (non condensing)
Storage: 20% to 85% (non condensing)



Physical

- Dimensions (WxDxH): 14.92 x 2.99 x 2.76 in (379.1 x 76 x 70 mm)
- Weight Body: 14.04 oz (398 g)
- Case: ABS, black

Regulatory and Safety

- Product Compliance: CE, FCC, RoHS

Sold Separately

- Power supply 12V / 3.5A, Euro Power cable C7, 2m, Ethernet cable

Copyright 2015 Opticon. All rights reserved. This information is subject to change without notice. For availability, contact your local representative.

- The Netherlands: Hoofddorp
- France: Issy Les Moulineaux
- Germany: Dietzenbach
- Italy: Castel Maggiore (BO)
- Sweden: Järfälla
- United Kingdom: Luton, Bedfordshire

- U.S.A.: Renton, WA
- Brazil: São Paulo
- Japan: Warabi City
- Taiwan: Taipei
- P.R.China: Shanghai

Opticon, Inc.
2220 Lind Ave. SW, Suite 100
Renton, WA 98057
Toll Free: 800.636.0090
Local: 425.651.2120
Fax: 425.454.0865
Email: Sales@OpticonUSA.com
Email: Support@OpticonUSA.com

OPTICON

WWW.OPTICONUSA.COM